

| Dimension | Weight | Packaging | Material No. | Condition | Tolerance | Length | End Finish |
|---|--------|-----------|--------------|-----------|-----------|--------|---------------------|
| | | | | | | | |
| eco SW1®, CuZn21Si3P, CW724R, EN 12164/C69300 | | | | | | | |
| Round rod, 3,000 mm | | | | | | | |
| 7.0 | 0.317 | ● | 479207000 | R670 | +0/-0.036 | ± 50 | chamfered/pointed |
| 8.0 | 0.415 | ● | 479208000 | | | | |
| 9.0 | 0.525 | ● | 479209000 | | | | |
| 10.0 | 0.648 | ○ | 479210000 | | | | |
| 11.0 | 0.784 | ○ | 479211000 | | | | |
| 12.0 | 0.933 | ○ | 479212000 | | | | |
| 13.0 | 1.095 | ○ | 479213000 | | | | |
| 14.0 | 1.270 | ○ | 479214000 | | | | |
| 15.0 | 1.458 | ○ | 479215000 | | | | |
| 16.0 | 1.659 | ○ | 479216000 | | | | |
| 17.0 | 1.873 | ○ | 479217000 | R600 | +0/-0.043 | ± 50 | chamfered/pointed |
| 18.0 | 2.099 | ○ | 479218000 | | | | |
| 19.0 | 2.339 | ○ | 479219000 | | | | |
| 20.0 | 2.592 | ○ | 479220000 | | | | |
| 22.0 | 3.136 | ○ | 479222000 | | | | |
| 23.0 | 3.428 | ○ | 479223000 | | | | |
| 24.0 | 3.732 | ○ | 479224000 | | | | |
| 25.0 | 4.050 | ○ | 479225000 | | | | |
| 27.0 | 4.724 | ○ | 479227000 | | | | |
| 28.0 | 5.080 | ○ | 479228000 | | | | |
| 30.0 | 5.832 | ○ | 479230000 | R500 | +0/-0.052 | ± 100 | both ends chamfered |
| 32.0 | 6.635 | ○ | 479232000 | | | | |
| 35.0 | 7.937 | ○ | 479235000 | | | | |
| 38.0 | 9.356 | ○ | 479238000 | | | | |
| 40.0 | 10.367 | ○ | 479240000 | | | | |
| 42.0 | 11.430 | ○ | 479242000 | | | | |
| 45.0 | 13.114 | ○ | 479245000 | | | | |
| 48.0 | 14.929 | ○ | 479248000 | | | | |
| 50.0 | 16.199 | ○ | 479250000 | | | | |

| Dimension | Weight | Packaging | Material No. | Condition | Tolerance | Length | End Finish |
|--|--------|-----------|--------------|-----------|-----------|--------|---------------------|
| | | | | | | | |
| ecobrass SW4®, CuZn21Si3P, CW724R, EN 12164/C69305 | | | | | | | |
| Round rod, 3,000 mm | | | | | | | |
| 10.0 | 0.649 | ● | 479610000 | R500 | +0/-0.036 | ± 50 | chamfered/pointed |
| 11.0 | 0.785 | ● | 479611000 | | | | |
| 12.0 | 0.934 | ● | 479612000 | | | | |
| 13.0 | 1.096 | ○ | 479613000 | | | | |
| 14.0 | 1.272 | ○ | 479614000 | | | | |
| 15.0 | 1.460 | ○ | 479615000 | | | | |
| 16.0 | 1.661 | ○ | 479616000 | | | | |
| 17.0 | 1.875 | ○ | 479617000 | | | | |
| 18.0 | 2.102 | ○ | 479618000 | | | | |
| 19.0 | 2.342 | ○ | 479619000 | | | | |
| 20.0 | 2.595 | ○ | 479620000 | R500 | +0/-0.043 | ± 50 | chamfered/pointed |
| 21.0 | 2.861 | ○ | 479621000 | | | | |
| 22.0 | 3.136 | ○ | 479622000 | | | | |
| 23.0 | 3.432 | ○ | 479623000 | | | | |
| 24.0 | 3.737 | ○ | 479624000 | | | | |
| 25.0 | 4.055 | ○ | 479625000 | | | | |
| 26.0 | 4.385 | ○ | 479626000 | | | | |
| 27.0 | 4.729 | ○ | 479627000 | | | | |
| 28.0 | 5.086 | ○ | 479628000 | | | | |
| 30.0 | 5.832 | ○ | 479630000 | | | | |
| 32.0 | 6.643 | ○ | 479632000 | R500 | +0/-0.052 | ± 100 | both ends chamfered |
| 33.0 | 7.065 | ○ | 479633000 | | | | |
| 34.0 | 7.490 | ○ | 479634000 | | | | |
| 35.0 | 7.947 | ○ | 479635000 | | | | |
| 38.0 | 9.356 | ○ | 479638000 | | | | |
| 40.0 | 10.367 | ○ | 479640000 | | | | |
| 45.0 | 13.121 | ○ | 479645000 | | | | |
| 48.0 | 14.929 | ○ | 479648000 | | | | |
| 50.0 | 16.199 | ○ | 479650000 | | | | |

Standard Packaging:

- = wooden boxes of approx. 500 kg,
≤ 5,5 mm in small bundles of 25 kg
- = bundles of approx. 500 kg,
alternatively bundles of approx. 1,000 kg are possible

| Dimension | Weight | Packaging | Material No. | Condition | Tolerance (class) | Length | End Finish |
|----------------------------------|--------|-----------|--------------|-----------|-------------------|--------|---------------------|
| | | | | | | | |
| eco SZ3 [®] , CuZn40SiP | | | | | | | |
| Round rod, 3,000 mm | | | | | | | |
| 3.0 | 0.060 | x | 444303000 | W-R520 | h9 | ± 50 | chamfered/pointed |
| 4.0 | 0.106 | x | 444304000 | | | | |
| 5.0 | 0.166 | x | 444305000 | | | | |
| 6.0 | 0.232 | ● | 444306000 | | | | |
| 7.0 | 0.316 | ● | 444307000 | | | | |
| 8.0 | 0.413 | ● | 444308000 | | | | |
| 9.0 | 0.522 | ● | 444309000 | | | | |
| 10.0 | 0.645 | ○ | 444310000 | | | | |
| 11.0 | 0.780 | ○ | 444311000 | | | | |
| 12.0 | 0.929 | ○ | 444312000 | | | | |
| 13.0 | 1.090 | ○ | 444313000 | | | | |
| 14.0 | 1.264 | ○ | 444314000 | | | | |
| 15.0 | 1.451 | ○ | 444315000 | | | | |
| 16.0 | 1.651 | ○ | 444316000 | | | | |
| 17.0 | 1.864 | ○ | 444317000 | | | | |
| 18.0 | 2.089 | ○ | 444318000 | | | | |
| 19.0 | 2.328 | ○ | 444319000 | | | | |
| 20.0 | 2.579 | ○ | 444320000 | | | | |
| 22.0 | 3.121 | ○ | 444322000 | | | | |
| 24.0 | 3.714 | ○ | 444324000 | | | | |
| 25.0 | 4.030 | ○ | 444325000 | | | | |
| 26.0 | 4.359 | ○ | 444326000 | | | | |
| 27.0 | 4.701 | ○ | 444327000 | | | | |
| 28.0 | 5.055 | ○ | 444328000 | | | | |
| 30.0 | 5.803 | ○ | 444330000 | | | | |
| 32.0 | 6.603 | ○ | 444332000 | | | | |
| 35.0 | 7.899 | ○ | 444335000 | | | | |
| 40.0 | 10.317 | ○ | 444340000 | | | | |
| 45.0 | 13.057 | ○ | 444345000 | | | | |
| 50.0 | 16.120 | ○ | 444350000 | | | | |
| 60.0 | 23.213 | ○ | 444360000 | | | | |
| | | | | W-R460 | h11 | ± 100 | both ends chamfered |

| Dimension | Weight | Packaging | Material No. | Condition | Tolerance (class) | End Finish |
|--|--------|-----------|--------------|-----------|-------------------|-------------------|
| | | | | | | |
| eco SZ4 [®] , CuZn42, CW510L, EN12164 | | | | | | |
| Round rod, 3,000 ± 50 mm | | | | | | |
| 4.0 | 0.103 | x | 444404000 | R500 | h9 | chamfered/pointed |
| 5.0 | 0.161 | x | 444405000 | | | |
| 6.0 | 0.232 | ● | 444406000 | | | |
| 8.0 | 0.412 | ● | 444408000 | | | |
| 10.0 | 0.644 | ○ | 444410000 | | | |
| 12.0 | 0.927 | ○ | 444412000 | | | |
| 14.0 | 1.262 | ○ | 444414000 | | | |
| 20.0 | 2.576 | ○ | 444420000 | | | |
| 30.0 | 5.796 | ○ | 444430000 | | | |
| | | | | | | |

Standard Packaging:

- x = wooden boxes of approx. 250 kg
- = wooden boxes of approx. 500 kg,
≤ 5,5 mm in small bundles of 25 kg
- = bundles of approx. 500 kg,
alternatively bundles of approx. 1,000 kg are possible