

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Länge	Endenausführung
mm	kg/m					mm	
eco SW1 [®] , CuZn21Si3P, CW724R, EN 12164/C69300							
Rundstange, 3.000 mm							
7,0	0,317	●	479207000	R670	+0/-0,036		
8,0	0,415	●	479208000				
9,0	0,525	●	479209000				
10,0	0,648	○	479210000				
11,0	0,784	○	479211000				
12,0	0,933	○	479212000				
13,0	1,095	○	479213000				
14,0	1,270	○	479214000	R600	+0/-0,043		
15,0	1,458	○	479215000				
16,0	1,659	○	479216000				
17,0	1,873	○	479217000				
18,0	2,099	○	479218000				
19,0	2,339	○	479219000				
20,0	2,592	○	479220000				
22,0	3,136	○	479222000	R500	+0/-0,052	± 50	
23,0	3,428	○	479223000				
24,0	3,732	○	479224000				
25,0	4,050	○	479225000				
27,0	4,724	○	479227000				
28,0	5,080	○	479228000				
30,0	5,832	○	479230000				
32,0	6,635	○	479232000	R500	+0/-0,16	± 100	
35,0	7,937	○	479235000				
38,0	9,356	○	479238000				
40,0	10,367	○	479240000				
42,0	11,430	○	479242000				
45,0	13,114	○	479245000				
48,0	14,929	○	479248000				
50,0	16,199	○	479250000			beidseitig angefast	

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Länge	Endenausführung
mm	kg/m					mm	
ecobrass SW4 [®] , CuZn21Si3P, CW724R, EN 12164/C69305							
Rundstange, 3.000 mm							
10,0	0,649	●	479610000	R500	+0/-0,036		
11,0	0,785	●	479611000				
12,0	0,934	●	479612000				
13,0	1,096	○	479613000				
14,0	1,272	○	479614000				
15,0	1,460	○	479615000				
16,0	1,661	○	479616000				
17,0	1,875	○	479617000	R500	+0/-0,043		
18,0	2,102	○	479618000				
19,0	2,342	○	479619000				
20,0	2,595	○	479620000				
21,0	2,861	○	479621000				
22,0	3,136	○	479622000				
23,0	3,432	○	479623000				
24,0	3,737	○	479624000	R500	+0/-0,052	± 50	
25,0	4,055	○	479625000				
26,0	4,385	○	479626000				
27,0	4,729	○	479627000				
28,0	5,086	○	479628000				
30,0	5,832	○	479630000				
32,0	6,643	○	479632000				
33,0	7,065	○	479633000	R500	+0/-0,16	± 100	
34,0	7,490	○	479634000				
35,0	7,947	○	479635000				
38,0	9,356	○	479638000				
40,0	10,367	○	479640000				
45,0	13,121	○	479645000				
48,0	14,929	○	479648000				
50,0	16,199	○	479650000			beidseitig angefast	

Standardverpackung:

- = in Holzkisten von ca. 500 kg,
≤ 5,5 mm in Kleinbunden von 25 kg
- = in Bunden von ca. 500 kg,
alternativ in Bunden von ca. 1.000 kg möglich

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranzklasse	Länge	Endenausführung
mm	kg/m					mm	
eco SZ3 [®] , CuZn40SiP							
Rundstange, 3.000 mm							
3,0	0,060	x	444303000	W-R520	h9	± 50	angefast/angespitzt
4,0	0,106	x	444304000				
5,0	0,166	x	444305000				
6,0	0,232	●	444306000				
7,0	0,316	●	444307000				
8,0	0,413	●	444308000				
9,0	0,522	●	444309000				
10,0	0,645	○	444310000				
11,0	0,780	○	444311000				
12,0	0,929	○	444312000				
13,0	1,090	○	444313000				
14,0	1,264	○	444314000				
15,0	1,451	○	444315000	W-R460	h11	± 100	beidseitig angefast
16,0	1,651	○	444316000				
17,0	1,864	○	444317000				
18,0	2,089	○	444318000				
19,0	2,328	○	444319000				
20,0	2,579	○	444320000				
22,0	3,121	○	444322000				
24,0	3,714	○	444324000				
25,0	4,030	○	444325000				
26,0	4,359	○	444326000				
27,0	4,701	○	444327000				
28,0	5,055	○	444328000				
30,0	5,803	○	444330000				
32,0	6,603	○	444332000				
35,0	7,899	○	444335000				
40,0	10,317	○	444340000				
45,0	13,057	○	444345000				
50,0	16,120	○	444350000				
60,0	23,213	○	444360000				

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranzklasse	Endenausführung			
mm	kg/m								
eco SZ4 [®] , CuZn42, CW510L, EN12164									
Rundstange, 3.000 ± 50 mm									
4,0	0,103	x	444404000	R500	h9	angefast/angespitzt			
5,0	0,161	x	444405000						
6,0	0,232	●	444406000						
8,0	0,412	●	444408000						
10,0	0,644	○	444410000						
12,0	0,927	○	444412000						
14,0	1,262	○	444414000						
20,0	2,576	○	444420000				R430		
30,0	5,796	○	444430000						

Standardverpackung:

x = in Holzkisten von ca. 250 kg

● = in Holzkisten von ca. 500 kg,

≤ 5,5 mm in Kleinbunden von 25 kg

○ = in Bunden von ca. 500 kg,

alternativ in Bunden von ca. 1.000 kg möglich